

# EURO CHARGER II

## STANDARD DUAL SYSTEM BATTERY CHARGER FOR EXPORT



MODEL # 091-117-12

The Euro Charger II is a fully automatic battery charger designed to meet CE requirements. Ruggedly constructed with a dual output, it float charges the battery and may be installed on the vehicle. Extremely precise voltage control maintains the charger output constant with variations in load or line voltage input. Active current limiting, limits the output current so as not to exceed its rated value when charging deeply discharged batteries or if the vehicle is started while charging.

### SPECIFICATIONS:

**Input:** 120/230 Vac, 50/60 Hz, 2.6/1.3 Amps Max

**Input Fuse:** 5 / 3 Amps, Fast Acting

**Output:** 12 Vdc, 12 Amps

**Output Fuse (Recommended):** 24 Amps

**Charge Indicator:** 0-15 Amps

**Weight:** 12 lbs

**Warranty:** 3 Years



ENERGIZED AND READY, WHEN SECONDS COUNT

**12 AMPS FOR CHARGING VEHICLE BATTERIES**

**INPUT VOLTAGE SELECTABLE, 115 or 230 VOLTS AC**

**DESIGNED TO MEET CE REQUIREMENTS**

**AUTOMATICALLY CHARGES DUAL BANKS OF BATTERIES**

**OPTIONAL REMOTE DISPLAYS**

**3 YEAR WARRANTY**

### OPTIONAL INDICATORS

#### BAR GRAPH DISPLAY



Model 091-11-127-12

10 Element,  
Weatherproof Dual  
Bar Graph battery  
condition display.

#### LOW COST LED INDICATOR



Model 091-90-012-12

LED Indicator shows  
when the charger is  
"ON" and when it is  
"CHARGING".

