

EURO CHARGER III

STANDARD TRIPLE SYSTEM BATTERY CHARGER FOR EXPORT



MODEL # 091-118-12

The Euro Charger III is a fully automatic battery charger designed to meet CE requirements. Ruggedly constructed with a triple output, it float charges the battery and may be installed on the vehicle. Extremely precise voltage control maintains the charger output constant with variations in load or line voltage input. Active current limiting, limits the output current so as not to exceed its rated value when charging deeply discharged batteries or if the vehicle is started while charging.

SPECIFICATIONS:

Input: 120/230 Vac, 50/60 Hz, 4.7/2.4 Amps Max

Input Fuse: 5 Amps, Fast Acting

Output: 12 Vdc, 18 Amps

Output Fuse (Recommended): 36 Amps

Charge Indicator: 0-25 Amps

Weight: 22 lbs

Warranty: 3 Years



ENERGIZED AND READY, WHEN SECONDS COUNT

18 AMPS FOR CHARGING VEHICLE BATTERIES

DESIGNED SPECIFICALLY FOR VEHICLES WITH TRIPLE BATTERY SYSTEMS

DESIGNED TO MEET CE REQUIREMENTS

INPUT VOLTAGE SELECTABLE, 115 OR 230 VOLTS

3 YEAR WARRANTY

OPTIONAL INDICATORS

BAR GRAPH DISPLAY



Model 091-118-022-12

10 Element, Weatherproof Triple Bar Graph battery condition display.

LOW COST LED INDICATOR



Model 091-90-012-12

LED Indicator shows when the charger is "ON" and when it is "CHARGING".

