

SUPER 30 AUTO EJECT - AE

30 AMP AIR-ELECTRIC AUTO EJECT

Features

- 30A, 250V, 175PSI
- Heavy duty pin and sleeve contacts provide reliable connection over years of insertion/eject cycles
- Air connection made through a brass fitting containing a shut-off valve
 - Shut-off valve opens when plug is inserted to supply air pressure to the vehicle
 - Shut-off valve closes automatically when plug is ejected sealing off the air supply air
- Upon sensing engine start, the plug ejects from receptacle and away from vehicle path; eliminating dangerous severing of cord
- Air-Electric energizing is delayed until detector pin senses plug is inserted, eliminating terminal arcing
- After eject, weatherproof cover snaps into position over inlet
- Smooth sculpted cover, no sharp edges
- Weatherproof back enclosure with watertight cable fittings protects mechanism from road contamination
- System includes: Air-Electric Eject, Cover, Plug, and 30' of Air Line
- 2 Year Warranty



Specifications:

Input Voltage (Volts DC): 10 - 28
Input Current (Amps): 1.6 max
Output Voltage (Volts AC): 250
Output Current (Amps): 30
Output Air Rating (PSI): 175
Output Fuse (Supplied with unit): 2 Amps
Weight (lbs.): 8
Warranty: 2 Years



Weatherproof Cover Color Options

| | |
|---------------------|---------------------|
| YW Yellow | WH White |
| RD Red | GY Gray |
| BL Blue | BLK Black |



Model #: 091-169-CON-4P-250
30A, 250V, 150PSI Plug

| Part Number | Description | Electrical Data | | | | | Dimensions | | | Wgt. |
|----------------|----------------------------------|-----------------|---------|----------|---------|-------------|------------|-------|-------|------|
| | | DC Volts | DC Amps | AC Volts | AC Amps | Maximum PSI | H | W | D | |
| 091-169-30-250 | Super 30 Air-Electric Auto Eject | 12 / 24 | 1.6 | 250 | 30 | 175 | 8.90" | 6.68" | 6.20" | 8 |