

AUTO CHARGE 80 LPC

LOW PROFILE CHARGER

Features

- 80 Amps for charging vehicle batteries
- Light weight, small low profile size
- Clean output poses no interference with radios and other mobile devices
- Auxiliary 15 Amp output circuit with power source selector switch for operating accessory loads: air compressor pumps, hand lights or handheld radios
- Front panel connections for remote display and auxiliary loads
- Designed for rigors of emergency vehicle use; heavy duty aluminum case
- Remote battery sensing output to compensate for longer charging cables




Remote Display Options




Bar Graph Display
091-206-12-IND
80A Charger & Display



**Status Center in
Watertight Case**
Color Options



091-206-12-194C-WT-XX
80A Charger & Display



Status Center Display
091-206-12-194C
80A Charger & Display

Specifications:

- Input Voltage (Volts AC): 120
- Input Current (Amp AC): 13
- Input Frequency (Hz): 50/60 Hz
- Output Voltage (Volts DC): 12
- Output Current (Amps DC): 80
- Output Fuse (Included): 100 Amps
- Weight (lbs.): 10
- Warranty: 3 Years

Part Number	Description	Electrical Data				Dimensions			Wt.
		DC Volts	DC Amps	AC Volts	AC Amps	L	W	D	
091-206-12-IND	LPC 80, w/ Bar Graph Display	12	80	120	13	13.75"	7.00"	4.09"	10
091-206-12-194C	LPC 80, w/ Status Center	12	80	120	13	13.75"	7.00"	4.09"	10
091-206-12-194C-WT-XX	LPC 80, w/ Watertight Display	12	80	120	13	13.75"	7.00"	4.09"	10