

# Auto Charge 7 LPC

## Low Profile Charger

### Features

- 7 Amps for charging vehicle batteries
- Three step charging: bulk, absorption, float
- Light weight, small low profile size
- Clean output poses no interference with radios and other mobile devices
- Gel cell/lead-acid switch selects optimum charge/float voltages based on battery type
- Charger Status indicator light—changes color according to output
- Current limiting prevents damage from overload
- Load activated cooling fan allows continuous operation at full-rated output
- Float / 3 Step selector switch protects batteries when charging under continuous load
- Meets CE requirements
- Designed for rigors of emergency vehicle use; heavy duty stainless steel case



### Specifications: Auto Charge 7 LPC

**Input Voltage (Volts AC):** 120/240

**Input Current (Amp AC):** 2.0/1.0

**Input Frequency (Hz):** 50/60 Hz

**Output Voltage (Volts DC):** 12

**Output Current (Amps DC):** 7

**Battery Capacity (Amp-Hours):** 14-70

**Output Fuse (Recommended):** 10 Amps

**Protection:** Input/Output Fuses, Current Limiting, Thermal Protection, Forced Air Cooling

**Weight (lbs.):** 4

**Warranty:** 3 Years

Part Number	Description	Electrical Data				Dimensions			Wgt.
		DC Volts	DC Amps	AC Volts	AC Amps	L	W	H	
445-4290-5	Auto Charge 7 LPC	12	7	120/240	2.0/1.0	8.62"	4.93"	2.47"	4