

















# CHARGER SELECTION GUIDE

SINGLE BATTERY BANK SYSTEMS SELECTION CHART																		
<div style="display: flex; flex-direction: column; align-items: flex-start;"> <div style="display: flex; align-items: center; margin-bottom: 5px;"> <div style="width: 15px; height: 15px; background-color: #90EE90; margin-right: 5px;"></div> Recommended                 </div> <div style="display: flex; align-items: center; margin-bottom: 5px;"> <div style="width: 15px; height: 15px; background-color: #FFFF00; margin-right: 5px;"></div> OK                 </div> <div style="display: flex; align-items: center;"> <div style="width: 15px; height: 15px; background-color: #FF0000; margin-right: 5px;"></div> Not Recommended                 </div> </div> <p style="margin-top: 10px;">Average Battery Ratings CCA: 700 Amp Hour: 100</p>																		
						PARASITIC LOADS IN AMPS												
CHARGER SERIES	AMPS	PAGE	0	5	10	0	5	10	0	5	10	0	5	10	20	0	5	10
<b>AUTO CHARGE CHIEF SERIES</b>																		
Chief Series 4012	40	10																
Chief Series 6012	60	10																
<b>AUTO CHARGE</b>																		
Auto Charge 12	12	11																
Auto Charge 12HO	20	11																
Auto Charge 1200	40	14																
<b>LOW PROFILE</b>																		
LPC 7	7	7																
LPC 20	20	9																
LPC 40	40	8																
LPC 80	80	9																
<b>EV</b>																		
EV-20	20	18																
EV-40	40	18																
<b>AUTO CHARGE - BATTERY SAVER</b>																		
Auto Charge 1000	18	12																
Auto Charge 20/20	40	13																
Auto Charge 35/10	45	16																
Auto Charge 40/20	60	17																
<b>WATERPROOF</b>																		
WP-35	35																	
<b>PUMP PLUS</b>																		
Pump Plus 1000 PLC	18	51																
Pump Plus 1200	40	52																

These chargers are for average recharge rates and average sized batteries. For specific applications, please contact our sales or engineering department with battery size, parasitic loads and required recharge time.

# CHARGER SELECTION GUIDE

DUAL BATTERY BANK SYSTEMS SELECTION CHART														
<p>  Recommended   OK   Not Recommended                 </p> <p>                     Average Battery Ratings                      CCA: 700                      Amp Hour: 100                 </p>												DDEC SYSTEMS 		
												MAIN BATTERY 		
			PARASITIC LOADS IN AMPS											
CHARGER SERIES	AMPS	PAGE	0	5	10	0	5	10	0	5	10	0	5	10
<b>AUTO CHARGE CHIEF SERIES</b>														
Chief Series 4012	40	10												
Chief Series 6012	60	10												
<b>AUTO CHARGE</b>														
Auto Charge 11	10	19												
Auto Charge 11HO	20	19												
<b>AUTO CHARGE / BATTERY SAVER</b>														
Auto Charge 2000 PLC	18	20												
<b>EURO</b>														
Euro II	12	24												
Euro II VHO	40	24												
<b>PUMP PLUS</b>														
Pump Plus HO	11	50												
Pump Plus 2000 PLC	18	53												

These chargers are for average recharge rates and average sized batteries. For specific applications, please contact our sales or engineering department with battery size, parasitic loads and required recharge time.